TT-MIXpro

NITROX

TRIMIX

FLOW BLENDING
from 50 l/min to 850 l/min
from 3 m³/h to 51 m³/h

NARDI
COMPRESSORI
BREATHING AIR

High

Precision
Quality
Performance
Money savings

INTELECTUAL PATENTED PROPERTY

NITROX - TRIMIX

NARDI COMPRESSORI BLENDING

TOUCH SCREEN DISPLAY

TT-MIXpro

TÜV SUD
ISO 9001

Quality system certified
to iso 9001

TT-MIX pro

The **NEW TT-MIX Pro** by *NARDI COMPRESSORI* is a versatile and easy-to-handle blending device for the filling and refills of your bottles. You have to simply set a precise and balanced mixture on the display and **TT-MIX Pro** will do all the work autonomously from the beginning until the final stage of the operation when the compressor stops. It is equipped with a double inlet for oxygen and helium, gas sensors, a touchscreen display with integrated software for automatic blending of mixtures and refills. It comes with a patented exclusive and unique system of automatic pressure and flow regulators. This fantastic system is an important asset for a good time management because you no longer have to supervise this operation, but you can go on with other assignments instead. The philosophy behind this amazing TT-MIX PRO is to offer maximum safety and total control of your blending activity.

All technical data may be changed
MADE IN ITALY BY NARDI COMPRESSORI
www.nardicompressori.com

1   Touch-Screen Display
2   Power Plug
3   I/O Power Switch
4   Air Inlet
5   Mixture Outlet (NITROX-TRIMIX , to be connected to compressor)
6   Helium Inlet Coupling (6 - 8 Bar/87 - 116 Psi)
7   Helium Inlet connection
8   Helium Sensor
9   Oxygen Inlet Coupling (6 - 8 Bar/87 - 116 Psi)
10   Oxygen Inlet connection
11   Oxygen Sensor
12   Mixer Tube
13   Cooling Fan
14   LAN or WI-FI Connection for PC and TABLET
15   Peripheral Connections
16   Oxygen Safety Valve
17   Helium Safety Valve
18   Bracket for wall mounting

The mixer can be connected to a modem or a LAN network, this way you can operate the mixer from a remote location with your PC, Tablet or Smartphone. You can monitor the mix or stop it at any time, wherever you are, using the NardiBlender computer software or by a direct connection using a remote access software such as VNC Viewer (also available as free apps for iOs and Android).

TECHNICAL FEATURES	
Automatic control with pressure regulators	Warning alarm and safety features activate when oxygen and helium finish
Automatic flow control of Oxygen and Helium	Gas alert safety device
Simple and intuitive	Constant and precise blending
Refilling of new mix without emptying bottles	Automatic control of compressor condensate drain
Automatic calculation of gas price of mixtures	Wireless modem with connections (Optional)
Can be connected to computers via LAN or Wireless	Switch for blending start-up (Optional)

MIXER Model	Type Mix	Flow blending		Material	Input	Max Consumption		Weight		Dimensions
Modello MISCELATORE	Tipo miscela	Portata miscela		Materiale	Voltaggio	Assorbimento		Peso		Dimensioni
Type	Gas	l/min.	m³/h	Type	VAC	Watt	Ampere	Kg	Lbs	cm (LxWxH)
TT-MIX PRO	Nitrox + Trimix	50 - 850	3 - 51	Stainless Steel	230/50-60	300	1,3	13,5	30	56 x 41 x 21

NARDI COMPRESSORI SRL

Via Marco Polo, 2
36075 Montecchio Maggiore (VI) ITALY

Phone   +39 0444 159111
Fax   +39 0444 159122